

LINEAR ADAPTOR

28- 35 -41 型 产品详细介绍

Input	AC 117 -120 - 220 -230V-240V 50Hz/60Hz	
Output	3V DC,0.05-1A	18V DC,0.05-0.6A
	4.5V DC,0.05-1A	19V DC,0.05-0.5A
	5V DC,0.05-0.8A	20V DC,0.05-0.5A
	6V DC,0.05-0.8A	21V DC,0.05-0.5A
	7.5V DC,0.05-0.8A	22V DC,0.05-0.5A
	8V DC,0.05-0.8A	23V DC,0.05-0.5A
	9V DC,0.05-0.8A	24V DC,0.05-0.5A
	10.5V DC,0.05-0.5A	
	11V DC,0.05-0.5A	
	12V DC,0.05-0.8A	
	13.5V DC,0.05-0.8A	
	14V DC, 0.05-0.8A	
	15V DC,0.05-0.8A	
	16V DC,0.05-0.65A	
	17V DC,0.05-0.75	
Safety	UL/CE EMC&LVD, EN60335, EN60950,EN61558-2-6	
Environmental	Operation temperature	0° C to + 40° C ambient
	Storage temperature	-10° C to + 70° C
	MTBF:>20,000 hours at full load and 25° C ambient temperature	
Weight	120-190g	